

Repairing or Installing a Fence in the Horse-Overlay Zone

Repairing an Existing Fence:

- Fences, walls, trellises and gates existing as of April 19, 2005, including those that are in the public right-of-way which may exceed 48 inches in height, may remain in their current location provided that they are maintained in good repair and are free of peeling and chipping paint.
- If you would like for your fence to remain in its' current location, it must be kept in good repair and must not be removed or replaced. Once it is removed, any new or replacement fence must meet the current standards for fences installed in the Horse-Overlay Zone, as noted below.

Installing a Fence Where None Existed Before:

New fences are allowed within the Horse-Overlay Zone, but must meet the following requirements according to (G.M.C. 30.21.040.E).

Fences and walls (over 18 inches high) within the street front setback and/or the street side setback:

- Shall be located on private property and shall be at least 5 feet from the street curb, and shall not exceed a height of 48 inches;
- May not be electrically charged or made of sharp-edged materials, barbed wire, razor wire, chicken wire, chain link, fiber glass, plain smooth block or painted block;
- Landscaping shall be provided between a fence/wall and the street; and
- Require a permit
-

Please contact Neighborhood Services to discuss repairing your old fence or for more information on installing a new fence, at (818) 548-3700.



***Glendale Municipal Code (GMC)30.21.040.E.**